



MATERIAL SAFETY DATA SHEET

FUSER WICK

Page 1 of 2

A-SP-ELMD044-AA-0 Rev A.

SECTION 1 - PREPARATION/PRODUCT INFORMATION

Manufacturer's Name: Digital Equipment Corporation Maynard, MA USA

Non-Emergency Phone Number: (508) 496-9242

Emergency Phone Numbers: 800-228-5635 ext.123
[+1] 612-221-3999 ext.123

Preparation Date: April 21, 1992

Supersedes: August 9, 1991

Product Name: Fuser Wick

Part Number(s): LN03X-AS

Use: For use with Image Transfer Device

SECTION 2 - INGREDIENTS

HAZARDOUS INGREDIENTS	CAS	%	ACGIH TLV	OSHA PEL	CARCINOGEN LIST			SARA 313
					IARC	NTP	OSHA	

None Fuser Wick is classified as an article. Wick contains fuser oil. See section 8 for Safe Handling/Preventive Measures.

All ingredients contained in this product are on the US TSCA inventory.

SECTION 3 - PHYSICAL AND CHEMICAL DATA

Boiling Point - Not applicable	Solubility in Water - < 0.1%
Vapor Pressure - Not applicable	Percent Volatile - None
Vapor Density - Not applicable	Evaporation Rate - Not applicable
Appearance - Plastic container with wick	Odor and Odor Threshold- None
Freezing Point - Not applicable	pH - Not applicable
Melting/Softening Point - Not applicable	Specific Gravity - Not applicable

SECTION 4 - FIRE AND EXPLOSION HAZARD

Flash Point - None	Special Fire Fighting Procedure - None
Auto-Ignition Temperature - Not applicable	Flammable Limits - None
Hazardous Combustion Products - Carbon monoxide, carbon dioxide	Extinguishing Media - Water, foam, dry chemical, carbon dioxide
Unusual Fire or Explosion Hazards - None	

SECTION 5 - REACTIVITY DATA

Stability - Stable

Incompatibility - None

Hazardous Decomposition Products - Not available

Hazardous Polymerization -None

Conditions to Avoid - Temperature above melting

SECTION 6 - HEALTH HAZARD DATA/TOXICOLOGICAL PROPERTIES

Hazard to Humans- Primary route of entry is dermal. Prolonged exposure can lead to accumulation of fuser oil on skin. No evidence of toxic response is expected. Potential exposure under normal use conditions should present no hazard.

Animal Experiment- (based on testing of fuser oil)

Acute- Oral LD50- >35 g/kg (practically non-toxic);

Dermal LD50- >2 g/kg;

Inhalation LC50- N.D. Non-irritating to skin and eyes.

Chronic/Other Will not cause sensitization, cancer, mutagenicity, or teratogenicity.

Additional Information- Aquatic LC₅₀ > 500mg/l.

SECTION 7 - EMERGENCY/FIRST AID PROCEDURE

(Applies to fuser oil)

If Inhaled - Not applicable.

If on Skin - Promptly wash skin with soap and water.

If in Eyes - Flush eyes with large quantities of water for at least 15 minutes.

If Swallowed- Seek immediate medical attention.

SECTION 8 - SAFE HANDLING/PREVENTIVE MEASURES

Personal Protective Equipment - None for normal use.

Engineer Control - Not needed.

Waste Disposal - No special Requirements.

Procedures for Leaks or Spills- Not applicable

Work Practices - None

Storage Requirement- Keep containers closed, store in cool, dry area.

Handling Procedure/Equipment- None

Labelling- None

WHMIS Classification- None

SECTION 9 - TRANSPORTATION REQUIREMENTS

None